



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	5.310	-58.5	50.60	-27.0	102.1	4.5	77.33	36.0	71.86	67.5	32.63
-88.5	6.206	-57.0	53.07	-25.5	103.9	6.0	77.94	37.5	70.41	69.0	31.08
-87.0	7.257	-55.5	55.73	-24.0	106.1	7.5	79.43	39.0	68.63	70.5	29.38
-85.5	8.351	-54.0	58.29	-22.5	107.4	9.0	80.06	40.5	66.69	72.0	27.69
-84.0	9.574	-52.5	60.83	-21.0	108.3	10.5	80.36	42.0	64.95	73.5	26.47
-82.5	11.02	-51.0	63.69	-19.5	108.3	12.0	80.22	43.5	62.78	75.0	24.88
-81.0	12.60	-49.5	66.11	-18.0	107.5	13.5	80.43	45.0	61.18	76.5	23.07
-79.5	14.40	-48.0	68.80	-16.5	106.4	15.0	80.82	46.5	58.86	78.0	21.05
-78.0	16.48	-46.5	71.45	-15.0	104.3	16.5	80.69	48.0	57.10	79.5	18.86
-76.5	19.06	-45.0	74.26	-13.5	101.7	18.0	81.11	49.5	55.92	81.0	16.29
-75.0	22.97	-43.5	77.17	-12.0	99.27	19.5	80.35	51.0	54.39	82.5	13.82
-73.5	26.58	-42.0	79.50	-10.5	96.63	21.0	79.46	52.5	52.65	84.0	11.26
-72.0	28.79	-40.5	81.33	-9.0	93.37	22.5	79.79	54.0	50.47	85.5	8.979
-70.5	30.80	-39.0	83.76	-7.5	90.12	24.0	79.53	55.5	48.52	87.0	7.652
-69.0	33.14	-37.5	86.03	-6.0	86.52	25.5	78.99	57.0	46.56	88.5	6.524
-67.5	35.40	-36.0	88.69	-4.5	83.57	27.0	78.52	58.5	44.46	90.0	5.594
-66.0	38.90	-34.5	91.72	-3.0	81.45	28.5	77.19	60.0	42.46		
-64.5	41.49	-33.0	93.88	-1.5	78.80	30.0	76.00	61.5	40.97		
-63.0	43.27	-31.5	97.16	0.0	77.13	31.5	75.15	63.0	40.05		
-61.5	46.10	-30.0	99.30	1.5	76.23	33.0	73.93	64.5	36.66		
-60.0	48.44	-28.5	100.5	3.0	76.87	34.5	73.02	66.0	34.41		

电学参数:

工作电流If: 20.00mA 工作电压vf: 1.989V
 反向漏电流Ir: 0.00μA (偏置Vr=5.00V)
 电功率P: 39.77mW

光学参数(CIE A):

平均光强扩散角: ?(25%): 145.7° ?(50%): 107.2° ?(75%): 37.4° ?(50%): 107.2°
 最大光强Imax = 108.5 mcd (C=0.0°,G=-20.2°)
 C0-180平面 Imax = 108.5 mcd (G=-20.2°) Io = 77.13 mcd

LED型号: EZDL3D625-5
 测试人员: Damin
 环境温度: 25.3
 制造厂商: Salens

产品编号: YZD20100721A1
 测试日期: 2010-10-27 LED620
 环境湿度: 65%
 备注: 样品质