

电化学式高精度酒精含量检测仪-PT500

产品功能

PT500 酒精含量检测仪。

PT500 酒精含量检测仪主要产品特点：

- 二级报警，报警点可调
- 具有两种单位供用户选择(mg/L，mg/100mL)
- 温度单位切换功能（华氏与摄氏）
- 吹气时间 1-8 秒可调
- 吹气中断提示功能
- 酒精浓度超限提示自动报警
- 点阵液晶屏显示，中文操作界面



PT500 酒精含量检测仪性能指标及主要技术参数：

- 传感器类型：燃料电池酒精传感器
- 工作电源：2 节 AA 电池
- 相对湿度：=95% (无凝露)
- 测试响应时间：< 20s
- 检测范围：0.000 ~ 1.000 mg/MI
- 报警浓度：0.020%BAC- 0.080%BAC 可调
- 检测精度： $< 0.40\text{mg/L} \quad \pm 0.02\text{mg/L}$
 $(0.40 \sim 1.00)\text{mg/L} \quad \pm 5\%$
 $=1.00\text{mg/L} \quad \pm 20\%$
- 显示方式：桔红色背光，点阵屏中文界面
- 重量：=160 g (含电池)
- 外形尺寸：128mm× 67mm × 32mm

Alcohol content Detector-PT500

PT500 alcohol tester main features:

Two level alarm, alarm point adjustable

With two units for the user to choose (mg/L, mg/100mL)

Temperature unit switching function (Fahrenheit and centigrade)

*1-8 seconds adjustable blowing time

,blowing interrupt function

Alcohol concentration exceeded tips, automatic alarm

,dot matrix LCD display, Chinese operation interface

The PT500 alcohol content detector performance and main technical parameters:

And sensor types: fuel cell alcohol sensor

The work of power: 2 AA batteries

And relative humidity: = 95% (no.)

Testing the response time: <20s

Detection range: 0~1 mg/MI

The concentration of 0.020%BAC- 0.080%BAC, alarm: adjustable

Detection precision: <0.40mg/L + 0.02mg/L

(0.40~1)mg/L + 5%

= 1.00mg/L + 20%

Display mode: orange, back light, LCD Chinese interface

Weight: 160 G (including battery)

,size: 128mm*67mm*32mm

