



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	1.040	-58.5	13.80	-27.0	29.83	4.5	26.13	36.0	26.63	67.5	12.42
-88.5	1.238	-57.0	14.33	-25.5	30.59	6.0	26.82	37.5	26.04	69.0	11.72
-87.0	1.594	-55.5	15.00	-24.0	31.07	7.5	27.53	39.0	25.57	70.5	11.04
-85.5	2.096	-54.0	15.90	-22.5	31.33	9.0	28.20	40.5	25.13	72.0	10.32
-84.0	2.545	-52.5	16.68	-21.0	31.82	10.5	28.95	42.0	24.64	73.5	9.374
-82.5	3.124	-51.0	17.42	-19.5	32.35	12.0	29.51	43.5	24.14	75.0	8.545
-81.0	3.548	-49.5	18.45	-18.0	32.63	13.5	29.84	45.0	23.35	76.5	7.966
-79.5	4.018	-48.0	19.66	-16.5	32.53	15.0	30.06	46.5	22.69	78.0	7.060
-78.0	4.562	-46.5	21.21	-15.0	32.37	16.5	30.24	48.0	22.18	79.5	6.065
-76.5	5.114	-45.0	22.05	-13.5	32.23	18.0	30.25	49.5	21.50	81.0	5.171
-75.0	5.755	-43.5	22.82	-12.0	31.82	19.5	30.13	51.0	20.70	82.5	4.324
-73.5	6.784	-42.0	23.64	-10.5	31.26	21.0	29.96	52.5	19.62	84.0	3.533
-72.0	7.748	-40.5	24.45	-9.0	30.45	22.5	29.90	54.0	18.21	85.5	2.898
-70.5	8.843	-39.0	25.08	-7.5	29.77	24.0	29.56	55.5	17.47	87.0	2.418
-69.0	9.758	-37.5	25.94	-6.0	28.92	25.5	29.43	57.0	16.71	88.5	2.030
-67.5	10.51	-36.0	26.63	-4.5	27.99	27.0	29.07	58.5	16.28	90.0	1.701
-66.0	11.37	-34.5	27.22	-3.0	27.03	28.5	28.75	60.0	16.25		
-64.5	12.02	-33.0	27.79	-1.5	26.14	30.0	28.40	61.5	15.64		
-63.0	12.69	-31.5	28.30	0.0	25.39	31.5	28.06	63.0	14.98		
-61.5	13.38	-30.0	28.57	1.5	25.16	33.0	27.56	64.5	14.23		
-60.0	13.73	-28.5	29.15	3.0	25.41	34.5	27.20	66.0	13.23		

电学参数:

工作电流If: 19.99mA 工作电压vf: 2.06V
 反向漏电流Ir: 0.00μA (偏置Vr=5.00V)
 电功率P: 41.09mW

光学参数(CIE A):

平均光强扩散角: ?(25%): 147.3° ?(50%): 112.8° ?(75%): 82.9° ?(50%): 112.8°
 最大光强Imax = 32.67 mcd (C=0.0°,G=-17.6°)
 C0-180平面 Imax = 32.67 mcd (G=-17.6°) Io = 25.39 mcd

LED型号: EZDL3D625-5
 测试人员: Damin
 环境温度: 25.3
 制造厂商: Salens

产品编号: YZD20100721A1
 测试日期: 2010-10-27 LED620
 环境湿度: 65%
 备注: 样品质