



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	1.555	-58.5	14.37	-27.0	24.32	4.5	25.21	36.0	23.65	67.5	12.00
-88.5	1.716	-57.0	15.04	-25.5	24.31	6.0	25.35	37.5	23.35	69.0	11.17
-87.0	1.987	-55.5	15.52	-24.0	24.30	7.5	25.55	39.0	22.93	70.5	10.42
-85.5	2.378	-54.0	15.96	-22.5	24.43	9.0	25.71	40.5	22.61	72.0	9.721
-84.0	2.802	-52.5	16.30	-21.0	24.53	10.5	25.76	42.0	22.33	73.5	8.992
-82.5	3.265	-51.0	16.77	-19.5	24.46	12.0	25.88	43.5	22.02	75.0	8.199
-81.0	3.739	-49.5	17.16	-18.0	24.51	13.5	26.13	45.0	21.55	76.5	7.267
-79.5	4.271	-48.0	17.73	-16.5	24.57	15.0	26.22	46.5	21.05	78.0	6.462
-78.0	4.815	-46.5	18.30	-15.0	24.68	16.5	26.16	48.0	20.43	79.5	5.687
-76.5	5.360	-45.0	18.99	-13.5	24.81	18.0	26.03	49.5	19.66	81.0	4.960
-75.0	5.972	-43.5	19.67	-12.0	24.76	19.5	26.00	51.0	19.08	82.5	4.273
-73.5	6.644	-42.0	20.22	-10.5	24.81	21.0	25.97	52.5	18.44	84.0	3.568
-72.0	7.493	-40.5	20.72	-9.0	24.74	22.5	25.98	54.0	17.93	85.5	2.955
-70.5	8.423	-39.0	21.11	-7.5	24.58	24.0	25.85	55.5	17.37	87.0	2.477
-69.0	9.477	-37.5	21.47	-6.0	24.59	25.5	25.78	57.0	16.76	88.5	2.142
-67.5	10.24	-36.0	21.91	-4.5	24.54	27.0	25.56	58.5	16.30	90.0	1.942
-66.0	11.00	-34.5	22.34	-3.0	24.61	28.5	25.18	60.0	15.65		
-64.5	12.01	-33.0	22.79	-1.5	24.73	30.0	24.96	61.5	14.96		
-63.0	12.67	-31.5	23.26	0.0	24.85	31.5	24.62	63.0	14.31		
-61.5	13.27	-30.0	23.62	1.5	24.86	33.0	24.27	64.5	13.54		
-60.0	13.89	-28.5	24.10	3.0	24.96	34.5	23.91	66.0	12.78		

电学参数:

工作电流If: 19.99mA      工作电压vf: 2.06V  
 反向漏电流Ir: 0.00μA      (偏置Vr=5.00V)  
 电功率P: 41.11mW

光学参数(CIE A):

平均光强扩散角:      ?(25%): 151.3°    ?(50%): 127.1°    ?(75%): 92.8°    ?(50%): 127.1°  
 最大光强Imax = 26.25 mcd (C=0.0°,G=14.4°)  
 C0-180平面 Imax = 26.25 mcd (G=14.4°) Io = 24.85 mcd

LED型号: EZDL3D625-5  
 测试人员: Damin  
 环境温度: 25.3  
 制造厂商: Salens

产品编号: YZD20100721A1  
 测试日期: 2010-10-27    LED620  
 环境湿度: 65%  
 备注: 样品质