



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	11.64	-58.5	35.51	-27.0	51.90	4.5	44.74	36.0	49.62	67.5	30.06
-88.5	12.08	-57.0	36.70	-25.5	51.86	6.0	45.06	37.5	49.31	69.0	28.68
-87.0	12.63	-55.5	37.97	-24.0	51.79	7.5	45.51	39.0	48.88	70.5	27.34
-85.5	13.42	-54.0	39.15	-22.5	51.60	9.0	45.92	40.5	48.31	72.0	26.06
-84.0	14.28	-52.5	40.31	-21.0	51.32	10.5	46.49	42.0	47.76	73.5	24.56
-82.5	15.17	-51.0	41.43	-19.5	50.98	12.0	47.01	43.5	47.09	75.0	23.23
-81.0	16.22	-49.5	42.52	-18.0	50.50	13.5	47.61	45.0	46.32	76.5	21.86
-79.5	17.38	-48.0	43.73	-16.5	50.03	15.0	48.06	46.5	45.66	78.0	20.54
-78.0	18.38	-46.5	44.57	-15.0	49.50	16.5	48.54	48.0	44.91	79.5	19.24
-76.5	19.52	-45.0	45.43	-13.5	48.95	18.0	49.00	49.5	44.15	81.0	18.09
-75.0	20.81	-43.5	46.42	-12.0	48.32	19.5	49.34	51.0	43.20	82.5	16.98
-73.5	22.04	-42.0	47.25	-10.5	47.58	21.0	49.72	52.5	42.16	84.0	15.99
-72.0	23.35	-40.5	48.08	-9.0	46.89	22.5	49.93	54.0	41.14	85.5	15.01
-70.5	24.75	-39.0	48.83	-7.5	46.28	24.0	50.13	55.5	40.09	87.0	14.10
-69.0	26.12	-37.5	49.58	-6.0	45.68	25.5	50.36	57.0	39.00	88.5	13.46
-67.5	27.36	-36.0	50.05	-4.5	45.15	27.0	50.48	58.5	37.82	90.0	13.10
-66.0	28.71	-34.5	50.59	-3.0	44.75	28.5	50.45	60.0	36.62		
-64.5	30.11	-33.0	51.00	-1.5	44.43	30.0	50.43	61.5	35.45		
-63.0	31.47	-31.5	51.39	0.0	44.27	31.5	50.36	63.0	34.20		
-61.5	32.81	-30.0	51.63	1.5	44.28	33.0	50.15	64.5	32.83		
-60.0	34.21	-28.5	51.77	3.0	44.47	34.5	49.95	66.0	31.40		

电学参数:

工作电流If: 19.99mA 工作电压vf: 2.05V
 反向漏电流Ir: 0.00μA (偏置Vr=5.00V)
 电功率P: 41.07mW

光学参数(CIE A):

平均光强扩散角: ?(25%): 176.3° ?(50%): 141.1° ?(75%): 111.2° ?(50%): 141.1°
 最大光强Imax = 51.93 mcd (C=0.0°,G=-25.8°)
 C0-180平面 Imax = 51.93 mcd (G=-25.8°) Io = 44.27 mcd

LED型号: EZDL3D625-5
 测试人员: Damin
 环境温度: 25.3
 制造厂商: Salens

产品编号: YZD20100721A1
 测试日期: 2010-10-27 LED620
 环境湿度: 65%
 备注: 样品质