



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	352.4	-58.5	361.6	-27.0	399.4	4.5	612.5	36.0	351.8	67.5	260.9
-88.5	462.7	-57.0	359.7	-25.5	405.7	6.0	613.1	37.5	351.3	69.0	254.8
-87.0	387.0	-55.5	362.4	-24.0	410.1	7.5	594.2	39.0	350.4	70.5	242.8
-85.5	380.3	-54.0	364.5	-22.5	417.6	9.0	557.7	40.5	343.9	72.0	228.0
-84.0	383.1	-52.5	367.6	-21.0	429.0	10.5	543.1	42.0	340.9	73.5	221.4
-82.5	383.5	-51.0	367.2	-19.5	449.7	12.0	531.0	43.5	336.1	75.0	214.1
-81.0	401.3	-49.5	369.8	-18.0	467.1	13.5	513.0	45.0	333.1	76.5	208.2
-79.5	449.9	-48.0	378.6	-16.5	482.4	15.0	482.7	46.5	328.7	78.0	276.7
-78.0	511.6	-46.5	387.3	-15.0	504.7	16.5	462.8	48.0	323.2	79.5	297.7
-76.5	314.1	-45.0	388.1	-13.5	532.2	18.0	454.3	49.5	319.4	81.0	261.3
-75.0	291.2	-43.5	389.6	-12.0	578.2	19.5	438.5	51.0	315.7	82.5	249.3
-73.5	300.9	-42.0	387.7	-10.5	596.7	21.0	417.0	52.5	311.8	84.0	248.7
-72.0	305.6	-40.5	385.9	-9.0	613.6	22.5	398.6	54.0	308.6	85.5	243.7
-70.5	312.8	-39.0	378.8	-7.5	616.8	24.0	391.2	55.5	301.4	87.0	233.6
-69.0	324.6	-37.5	378.3	-6.0	611.3	25.5	387.1	57.0	293.4	88.5	235.1
-67.5	331.1	-36.0	384.2	-4.5	613.8	27.0	385.3	58.5	290.0	90.0	316.0
-66.0	336.3	-34.5	389.5	-3.0	604.7	28.5	379.2	60.0	288.8		
-64.5	342.3	-33.0	386.8	-1.5	595.6	30.0	372.6	61.5	285.0		
-63.0	351.6	-31.5	389.0	0.0	597.3	31.5	369.7	63.0	279.0		
-61.5	359.5	-30.0	392.1	1.5	605.8	33.0	365.9	64.5	274.1		
-60.0	364.0	-28.5	393.6	3.0	610.8	34.5	358.5	66.0	269.1		

电学参数:

工作电流If: 19.99mA 工作电压vf: 2.09V
 反向漏电流Ir: 0.00μA (偏置Vr=5.00V)
 电功率P: 41.88mW

光学参数(CIE A):

平均光强扩散角: ?(25%): 180.0° ?(50%): 180.0° ?(75%): 105.3° ?(50%): 180.0°
 最大光强Imax = 617.2 mcd (C=0.0°,G=-8.0°)
 C0-180平面 Imax = 617.2 mcd (G=-8.0°) Io = 597.3 mcd

LED型号: EZDL3D625-5
 测试人员: Damin
 环境温度: 25.3
 制造厂商: Salens

产品编号: YZD20100721A1
 测试日期: 2010-10-27 LED620
 环境湿度: 65%
 备注: 样品质