



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	0.9467	-58.5	5.047	-27.0	11.45	4.5	13.18	36.0	7.686	67.5	3.728
-88.5	2.002	-57.0	5.164	-25.5	11.70	6.0	12.67	37.5	7.404	69.0	3.536
-87.0	3.065	-55.5	5.216	-24.0	11.80	7.5	12.25	39.0	6.975	70.5	3.338
-85.5	3.505	-54.0	5.338	-22.5	12.05	9.0	11.91	40.5	6.731	72.0	3.116
-84.0	2.993	-52.5	5.537	-21.0	12.55	10.5	11.77	42.0	6.472	73.5	2.958
-82.5	2.828	-51.0	5.709	-19.5	12.74	12.0	11.51	43.5	6.211	75.0	2.786
-81.0	2.972	-49.5	5.860	-18.0	12.77	13.5	11.31	45.0	5.954	76.5	2.776
-79.5	3.189	-48.0	6.077	-16.5	12.80	15.0	11.20	46.5	5.766	78.0	2.714
-78.0	3.418	-46.5	6.430	-15.0	13.08	16.5	11.09	48.0	5.565	79.5	2.609
-76.5	3.676	-45.0	6.875	-13.5	13.26	18.0	10.78	49.5	5.454	81.0	2.533
-75.0	3.870	-43.5	7.284	-12.0	13.41	19.5	10.36	51.0	5.386	82.5	2.406
-73.5	3.690	-42.0	7.667	-10.5	13.50	21.0	9.911	52.5	5.271	84.0	2.340
-72.0	3.889	-40.5	8.187	-9.0	13.40	22.5	9.494	54.0	5.169	85.5	2.229
-70.5	4.026	-39.0	8.587	-7.5	13.41	24.0	9.154	55.5	5.060	87.0	2.090
-69.0	4.085	-37.5	8.924	-6.0	13.71	25.5	8.989	57.0	5.002	88.5	2.009
-67.5	4.246	-36.0	9.257	-4.5	14.10	27.0	8.860	58.5	4.857	90.0	1.448
-66.0	4.393	-34.5	9.597	-3.0	14.41	28.5	8.848	60.0	4.668		
-64.5	4.512	-33.0	9.972	-1.5	14.42	30.0	8.706	61.5	4.468		
-63.0	4.626	-31.5	10.28	0.0	14.27	31.5	8.415	63.0	4.267		
-61.5	4.741	-30.0	10.66	1.5	13.99	33.0	8.136	64.5	4.121		
-60.0	4.893	-28.5	11.06	3.0	13.64	34.5	7.937	66.0	3.943		

电学参数:

工作电流If: 19.99mA 工作电压vf: 3.18V
 反向漏电流Ir: 0.00μA (偏置Vr=5.00V)
 电功率P: 63.65mW

光学参数(CIE A):

平均光强扩散角: ?(25%): 154.6° ?(50%): 81.6° ?(75%): 47.2° ?(50%): 81.6°
 最大光强Imax = 14.44 mcd (C=0.0°,G=-2.6°)
 C0-180平面 Imax = 14.44 mcd (G=-2.6°) Io = 14.27 mcd

LED型号: EZDL3D625-5
 测试人员: Damin
 环境温度: 25.3
 制造厂商: Salens

产品编号: YZD20100721A1
 测试日期: 2010-10-27 LED620
 环境湿度: 65%
 备注: 样品质