



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	7.280	-58.5	17.01	-27.0	50.05	4.5	216.6	36.0	64.78	67.5	12.07
-88.5	10.81	-57.0	16.07	-25.5	53.48	6.0	203.6	37.5	52.87	69.0	10.57
-87.0	10.99	-55.5	15.92	-24.0	56.44	7.5	189.1	39.0	44.25	70.5	9.433
-85.5	11.75	-54.0	16.38	-22.5	60.29	9.0	170.7	40.5	44.54	72.0	8.870
-84.0	12.22	-52.5	16.52	-21.0	58.30	10.5	156.6	42.0	38.23	73.5	7.480
-82.5	14.03	-51.0	18.00	-19.5	70.40	12.0	149.6	43.5	35.64	75.0	6.005
-81.0	14.22	-49.5	19.45	-18.0	65.48	13.5	138.4	45.0	31.34	76.5	5.578
-79.5	14.62	-48.0	20.21	-16.5	72.49	15.0	127.9	46.5	26.00	78.0	5.365
-78.0	15.70	-46.5	21.41	-15.0	75.57	16.5	104.0	48.0	22.48	79.5	5.662
-76.5	16.04	-45.0	23.51	-13.5	80.97	18.0	96.92	49.5	19.12	81.0	11.68
-75.0	17.03	-43.5	25.35	-12.0	87.95	19.5	91.12	51.0	15.86	82.5	9.587
-73.5	17.32	-42.0	27.80	-10.5	93.28	21.0	87.13	52.5	14.44	84.0	8.347
-72.0	17.73	-40.5	30.76	-9.0	48.53	22.5	84.13	54.0	16.60	85.5	6.871
-70.5	19.59	-39.0	33.54	-7.5	5.601	24.0	72.23	55.5	13.56	87.0	5.760
-69.0	20.16	-37.5	35.66	-6.0	273.4	25.5	1.555	57.0	11.65	88.5	5.672
-67.5	22.85	-36.0	37.99	-4.5	266.1	27.0	123.4	58.5	11.56	90.0	4.959
-66.0	19.30	-34.5	38.65	-3.0	263.1	28.5	91.48	60.0	9.105		
-64.5	15.81	-33.0	36.50	-1.5	263.0	30.0	81.50	61.5	14.71		
-63.0	15.72	-31.5	37.54	0.0	232.9	31.5	79.60	63.0	15.77		
-61.5	16.94	-30.0	39.80	1.5	278.7	33.0	69.00	64.5	14.34		
-60.0	17.09	-28.5	39.00	3.0	237.3	34.5	62.72	66.0	13.43		

电学参数:

工作电流If: 20.00mA 工作电压vf: 2.84V  
 反向漏电流Ir: 101.65μA (偏置Vr=5.00V)  
 电功率P: 56.88mW

光学参数(CIE A):

平均光强扩散角: ?(25%): 49.1° ?(50%): 20.2° ?(75%): 11.2° ?(50%): 20.2°  
 最大光强Imax = 289.6 mcd (C=0.0°,G=-6.6°)  
 C0-180平面 Imax = 289.6 mcd (G=-6.6°) Io = 232.9 mcd

LED型号: EZDL3D625-5  
 测试人员: Damin  
 环境温度: 25.3  
 制造厂商: Salens

产品编号: YZD20100721A1  
 测试日期: 2010-10-27 LED620  
 环境湿度: 65%  
 备注: 样品质