



光强分布数据:(角度°, 光强mcd) C0-180

| 角度 | 光强 | 角度 | 光强 | 角度 | 光强 | 角度 | 光强 | 角度 | 光强 | 角度 | 光强 |
|-------|-------|-------|-------|-------|-------|------|-------|------|-------|------|-------|
| -90.0 | 9.965 | -58.5 | 108.0 | -27.0 | 89.25 | 4.5 | 2467 | 36.0 | 91.08 | 67.5 | 113.2 |
| -88.5 | 11.80 | -57.0 | 77.97 | -25.5 | 91.42 | 6.0 | 1418 | 37.5 | 89.74 | 69.0 | 101.5 |
| -87.0 | 13.15 | -55.5 | 68.82 | -24.0 | 94.84 | 7.5 | 367.3 | 39.0 | 88.28 | 70.5 | 91.18 |
| -85.5 | 14.08 | -54.0 | 63.34 | -22.5 | 96.65 | 9.0 | 231.4 | 40.5 | 88.50 | 72.0 | 80.08 |
| -84.0 | 18.27 | -52.5 | 62.63 | -21.0 | 97.37 | 10.5 | 212.7 | 42.0 | 87.28 | 73.5 | 71.77 |
| -82.5 | 22.14 | -51.0 | 61.97 | -19.5 | 99.57 | 12.0 | 114.9 | 43.5 | 85.26 | 75.0 | 66.41 |
| -81.0 | 27.27 | -49.5 | 63.21 | -18.0 | 103.3 | 13.5 | 93.64 | 45.0 | 83.00 | 76.5 | 59.26 |
| -79.5 | 31.44 | -48.0 | 65.43 | -16.5 | 111.0 | 15.0 | 87.30 | 46.5 | 81.06 | 78.0 | 51.81 |
| -78.0 | 34.37 | -46.5 | 68.58 | -15.0 | 124.7 | 16.5 | 85.06 | 48.0 | 79.47 | 79.5 | 46.13 |
| -76.5 | 41.42 | -45.0 | 70.70 | -13.5 | 141.7 | 18.0 | 86.24 | 49.5 | 78.41 | 81.0 | 42.60 |
| -75.0 | 45.90 | -43.5 | 70.11 | -12.0 | 166.3 | 19.5 | 87.61 | 51.0 | 76.60 | 82.5 | 38.56 |
| -73.5 | 53.54 | -42.0 | 71.82 | -10.5 | 238.9 | 21.0 | 97.93 | 52.5 | 74.44 | 84.0 | 32.70 |
| -72.0 | 62.73 | -40.5 | 75.67 | -9.0 | 826.5 | 22.5 | 96.59 | 54.0 | 72.05 | 85.5 | 29.03 |
| -70.5 | 72.11 | -39.0 | 78.52 | -7.5 | 1858 | 24.0 | 92.31 | 55.5 | 70.46 | 87.0 | 26.66 |
| -69.0 | 88.98 | -37.5 | 79.55 | -6.0 | 3047 | 25.5 | 94.11 | 57.0 | 75.20 | 88.5 | 24.51 |
| -67.5 | 108.8 | -36.0 | 82.50 | -4.5 | 5197 | 27.0 | 92.92 | 58.5 | 76.82 | 90.0 | 22.09 |
| -66.0 | 129.2 | -34.5 | 85.08 | -3.0 | 6656 | 28.5 | 91.22 | 60.0 | 86.60 | | |
| -64.5 | 153.1 | -33.0 | 86.63 | -1.5 | 6398 | 30.0 | 91.56 | 61.5 | 95.69 | | |
| -63.0 | 169.5 | -31.5 | 86.99 | 0.0 | 6692 | 31.5 | 91.94 | 63.0 | 112.4 | | |
| -61.5 | 185.8 | -30.0 | 86.87 | 1.5 | 6056 | 33.0 | 92.18 | 64.5 | 133.0 | | |
| -60.0 | 149.3 | -28.5 | 87.94 | 3.0 | 3766 | 34.5 | 91.45 | 66.0 | 123.4 | | |

电学参数:

工作电流If: 19.95mA 工作电压vf: 2.06V
 反向漏电流Ir: 0.00μA (偏置Vr=5.00V)
 电功率P: 41.05mW

光学参数(CIE A):

平均光强扩散角: ?(25%): 13.3° ?(50%): 9.0° ?(75%): 6.6° ?(50%): 9.0°
 最大光强Imax = 6779 mcd (C=0.0°,G=0.4°)
 C0-180平面 Imax = 6779 mcd (G=0.4°) Io = 6692 mcd

LED型号: EZDL3D625-5
 测试人员: Damin
 环境温度: 25.3
 制造厂商: Salens

产品编号: YZD20100721A1
 测试日期: 2010-10-27 LED620
 环境湿度: 65%
 备注: 样品质