



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	3.135	-58.5	48.10	-27.0	95.85	4.5	91.71	36.0	95.08	67.5	33.10
-88.5	3.613	-57.0	51.94	-25.5	96.64	6.0	93.44	37.5	93.76	69.0	29.81
-87.0	4.241	-55.5	55.87	-24.0	97.43	7.5	95.33	39.0	92.65	70.5	26.69
-85.5	5.002	-54.0	59.90	-22.5	98.52	9.0	96.90	40.5	90.90	72.0	23.73
-84.0	6.009	-52.5	63.47	-21.0	98.59	10.5	98.21	42.0	89.32	73.5	21.16
-82.5	7.109	-51.0	67.10	-19.5	98.71	12.0	99.30	43.5	87.73	75.0	18.56
-81.0	8.334	-49.5	70.25	-18.0	98.28	13.5	100.1	45.0	86.12	76.5	16.39
-79.5	9.641	-48.0	73.28	-16.5	97.74	15.0	101.1	46.5	84.09	78.0	14.21
-78.0	11.20	-46.5	75.91	-15.0	96.94	16.5	101.6	48.0	82.06	79.5	12.30
-76.5	12.92	-45.0	78.61	-13.5	95.84	18.0	101.5	49.5	79.46	81.0	10.55
-75.0	14.86	-43.5	80.70	-12.0	94.75	19.5	101.6	51.0	76.41	82.5	8.912
-73.5	16.93	-42.0	82.83	-10.5	93.87	21.0	101.4	52.5	72.65	84.0	7.535
-72.0	19.20	-40.5	84.44	-9.0	93.29	22.5	101.3	54.0	68.78	85.5	6.244
-70.5	21.75	-39.0	86.26	-7.5	92.29	24.0	101.4	55.5	64.58	87.0	5.195
-69.0	24.35	-37.5	87.68	-6.0	91.12	25.5	101.0	57.0	60.69	88.5	4.208
-67.5	27.19	-36.0	89.44	-4.5	90.68	27.0	100.7	58.5	56.70	90.0	3.691
-66.0	30.14	-34.5	90.34	-3.0	90.01	28.5	100.7	60.0	52.32		
-64.5	33.49	-33.0	91.50	-1.5	89.37	30.0	100.1	61.5	47.97		
-63.0	36.97	-31.5	92.82	0.0	88.90	31.5	99.12	63.0	43.94		
-61.5	40.52	-30.0	94.08	1.5	89.24	33.0	97.75	64.5	40.34		
-60.0	44.18	-28.5	95.03	3.0	90.28	34.5	96.46	66.0	36.59		

电学参数:

工作电流If: 20.00mA      工作电压vf: 1.973V  
 反向漏电流Ir: 0.00μA      (偏置Vr=5.00V)  
 电功率P: 39.47mW

光学参数(CIE A):

平均光强扩散角:      ?(25%): 139.5°    ?(50%): 117.9°    ?(75%): 97.3°    ?(50%): 117.9°  
 最大光强Imax = 101.6 mcd (C=0.0°,G=17.4°)  
 C0-180平面 Imax = 101.6 mcd (G=17.4°) Io = 88.90 mcd

LED型号: EZDL3D625-5  
 测试人员: Damin  
 环境温度: 25.3  
 制造厂商: Salens

产品编号: YZD20100721A1  
 测试日期: 2010-10-27    LED620  
 环境湿度: 65%  
 备注: 样品质