



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	0.4207	-58.5	15.68	-27.0	22.65	4.5	694.7	36.0	19.97	67.5	16.65
-88.5	0.4909	-57.0	10.36	-25.5	22.69	6.0	696.0	37.5	18.26	69.0	17.93
-87.0	0.7008	-55.5	11.35	-24.0	23.24	7.5	423.2	39.0	17.17	70.5	17.95
-85.5	1.187	-54.0	11.64	-22.5	29.35	9.0	215.8	40.5	17.13	72.0	16.88
-84.0	1.863	-52.5	12.12	-21.0	30.46	10.5	129.4	42.0	16.81	73.5	13.60
-82.5	2.797	-51.0	13.15	-19.5	30.48	12.0	249.2	43.5	16.32	75.0	11.16
-81.0	3.587	-49.5	13.07	-18.0	33.54	13.5	218.6	45.0	16.30	76.5	8.745
-79.5	4.400	-48.0	14.16	-16.5	83.61	15.0	120.4	46.5	16.43	78.0	6.410
-78.0	5.019	-46.5	15.18	-15.0	136.3	16.5	107.1	48.0	15.73	79.5	5.757
-76.5	5.502	-45.0	16.31	-13.5	171.4	18.0	35.12	49.5	14.45	81.0	5.371
-75.0	7.080	-43.5	16.82	-12.0	315.9	19.5	25.65	51.0	13.37	82.5	4.250
-73.5	8.582	-42.0	17.07	-10.5	125.3	21.0	22.62	52.5	12.38	84.0	3.157
-72.0	10.40	-40.5	17.69	-9.0	187.6	22.5	21.83	54.0	12.01	85.5	2.461
-70.5	13.79	-39.0	18.39	-7.5	324.6	24.0	22.59	55.5	11.41	87.0	1.954
-69.0	15.80	-37.5	20.29	-6.0	609.5	25.5	23.20	57.0	10.74	88.5	1.642
-67.5	20.73	-36.0	20.40	-4.5	715.6	27.0	23.73	58.5	11.01	90.0	1.305
-66.0	23.68	-34.5	19.07	-3.0	758.3	28.5	23.35	60.0	10.47		
-64.5	19.87	-33.0	19.93	-1.5	905.7	30.0	22.37	61.5	16.65		
-63.0	21.09	-31.5	20.82	0.0	908.0	31.5	22.69	63.0	16.90		
-61.5	17.47	-30.0	22.06	1.5	927.7	33.0	23.15	64.5	16.75		
-60.0	17.92	-28.5	22.85	3.0	844.2	34.5	21.36	66.0	17.16		

电学参数:

工作电流If: 20.00mA 工作电压vf: 1.991V
 反向漏电流Ir: 0.00μA (偏置Vr=5.00V)
 电功率P: 39.83mW

光学参数(CIE A):

平均光强扩散角: $\theta(25\%)$: 26.3° $\theta(50\%)$: 13.9° $\theta(75\%)$: 11.3° $\theta(50\%)$: 13.9°
 最大光强Imax = 929.2 mcd (C=0.0°,G=1.7°)
 C0-180平面 Imax = 929.2 mcd (G=1.7°) Io = 908.0 mcd

LED型号: EZDL3D625-5
 测试人员: Damin
 环境温度: 25.3
 制造厂商: Salens

产品编号: YZD20100721A1
 测试日期: 2010-10-27 LED620
 环境湿度: 65%
 备注: 样品质